

PRODUCT INFORMATION



KG9 SERIES BULKHEAD FITTING GLAND

- High levels of EMC performance
- Overall screening is provided by reworkable band clamp
- Individual screening by interwoven braid and slotted body
- Termination by simple manual process
- Lightweight and compact in aluminium suitable for all panel applications
- Sealing by o-ring seal and heat shrink boot


The **KG9** series is part of the **KG** range of high performance, bulkhead glands. A variety of used techniques are to provide electromagnetic compatibility, including level performance, TEMPEST both individual and overall screening and environmental protection.

Suitable for both highly sophisticated and simpler solutions, the KG range is available at prices that are viable for small batch to high volume production runs. The range is ideal for all defence and aerospace as well as commercial and industrial applications.

KEC Limited is an EMC interconnect specialist that manufactures a wide selection of backshells, bulkhead/panel glands, conduit and conduit fittings and system harnesses.

KEC products are designed to suit all levels of screening requirements for EMI/RFI, EMP, TEMPEST and environmental protection and are designed to help manufacturers comply with UK and EC screening directives.

KG9 BULKHEAD GLAND








TABLE 1

| 1 | MATERIAL CODE | | | | | |
|----|-----------------|--|--|--|--|--|
| 01 | ALUMINIUM | | | | | |
| 02 | STAINLESS STEEL | | | | | |
| 03 | ALI BRONZE | | | | | |

TABLE 3

| | IADLL 3 | |
|------|--------------------------|--|
| CODE | DESCRIPTION | |
| G | BLACK ZINC NICKEL | |
| J | ELECTROLESS NICKEL | |
| W | CADMIUM + OLIVE DRAB | |
| Z | ZINC COBALT + OLIVE DRAB | |

TABLE 2

| ENTRY CODE | MAX CABLE ACCOMMODATION | Ø A | PANEL CUT-OUT DIMENSIONS | | OVERALL LENGTH |
|---------------|----------------------------|------|-----------------------------|------|-------------------|
| | | | Х | Υ | |
| 08 | 7.5 | 28.5 | 16.1 | 7.4 | |
| 10 | 9.3 | 31.8 | 19.3 | 8.9 | |
| 12 | 12.7 | 34.8 | 22.5 | 10.5 | |
| 14 | 14.4 | 38.1 | 25.6 | 12.0 | |
| 16 | 17.8 | 41.2 | 28.8 | 13.6 | 41.0 |
| 18 | 19.6 | 44.5 | 32.0 | 15.3 | |
| 20 | 24.1 | 47.5 | 35.2 | 16.9 | |
| 22 | 27.0 | 50.8 | 38.4 | 18.5 | |
| 24 | 29.2 | 53.8 | 41.5 | 20.0 | |

NOTES:

- 1. THE ABOVE INFORMATION IS TYPICAL AND MANY OTHER OPTIONS & VARIATIONS ARE AVAILABLE, PLEASE CONSULT FACTORY.
- 2. KG9 SUPPLIED WITH REWORKABLE BAND CLAMP & BRAID.
- 3. APPLICABLE PANEL THICKNESS RANGE: 1.4mm TO 9.5mm
- 4. CONSULT FACTORY IF REQUIRED.

04/20

KEC LIMITED

Orpheus House, Calleva Park, Aldermaston, Reading, Berkshire RG7 8TA England Tel: +44 (0)118 981 1571 Fax: +44 (0)118 981 1570 email: sales@kec.co.uk www.kec.co.uk